



Non-Electric Shock Tube System

Non-Electric Shock Tube System is a safe alternative to electric initiation. Shock tube is a plastic, hollow tube containing a thin layer of energetic materials with an attached firing device and detonator. At initiation, the shock tube transmits a signal to an output charge. Fully integrated with an attached in-line initiator firing device and detonator providing safe and reliable initiation.

APPLICATION:

The Shock Tube System is designed to initiate explosives and other energetic materials. The detonator is compatible with munitions, cap wells, detonating cords, high explosives and shock tube.

- Military demolitions
- Explosive ordnance disposal
- Minefield clearance
- Explosive testing
- Breaching
- Special applications

PROPERTIES:

- Safe alternative to electric initiation
- Water resistant detonator
- Available in varied lengths
- Military strength detonators
- Single and Dual shock tube lines
- 2 mm (0.083") or 3 mm (0.118") diameter
- Compact systems minimize logistical space
- 1.4S configuration for ease of transport
- Increased reliability with dual shock tube
- 40% reduction in weight and volume

NON ELECTRIC SHOCK TUBE SYSTEM:



MSDS No:
MSDSD10416/1

EX-2001100016, EX-2001100017
EX-2001100018, EX-2001100019
Detonator assemblies, Non-electric
UN0500 1.4S

NON-ELECTRIC SHOCK TUBE SYSTEM

AVAILABLE CONFIGURATIONS*

PICTURE	CONFIGURATION	SHOCK TUBE LENGTH	SINGLE OR DUAL SHOCK TUBE	SHOCK TUBE DIAMETER	INITIATION END	OUTPUT END MILITARY STRENGTH	TUBE COLOR	PACKAGING
	Spool	33' to 2500' (10 m to 760 m)	Single or Dual	2 mm or 3 mm	M81 firing device	Instant Detonator	Olive Green	Fiberboard Box
	Figure 80	10' to 50' (3 m to 15 m)	Single			Delay Detonator, 3.8 sec	Clear	
	Fan Pack	16' to 60' (5 m to 20 m)	Dual			In Line Initiator*	Blue (training only)	Wood Box
					Heat Seal	Delay Detonator, 6.4 sec	Bronze (inert only)	Metal Can
						Delay Detonator, 9.6 sec		
						Heat Seal		

*Other delay times available upon request

OPERATIONAL STEPS:

1. Connect detonator to explosive charge
2. Deploy shock tube while retreating to secure location
3. Initiate shock tube with the M81 (or other) firing device

PACKAGING:

- Military Packaging: Metal Ammunition Box or Wood Box
- Commercial Packaging: Fiberboard Box



ENSIGN-BICKFORD AEROSPACE & DEFENSE COMPANY
640 HOPMEADOW STREET, P.O. BOX 429, SIMSBURY, CT 06070, USA www.EBAD.com

This product and its components are protected under U.S. Patent Numbers 490,554 / 7,086,335 / 7,162,957 / 7,650,993 as well as a licensed Dyno Nobel Inc. U.S. Patent Number 5,597,974 and 5,365,851.

Attention: The information and recommendations described in this brochure cannot possibly cover every application of the products or variation of conditions under which the products are used. The recommendations herein are based on the manufacturer's experience, research and testing. They are believed to be accurate, but no warranties are made, express or implied. In addition, the specifications contained herein are all nominal which represent our current production. The products described may be subject to change. Please feel free to contact Ensign-Bickford Aerospace & Defense Company for verification. No Warranties or Liabilities: THE PRODUCTS DESCRIBED HEREIN are sold "AS IS" and without any warranty or guaranty, express, or implied, arising by law or otherwise including without limitation any warranty of merchantability or fitness for a particular purpose. Buyer and user agree further to release and discharge seller from any and all liabilities whatsoever arising out of the purchase or use of any product described herein whether or not such liability is occasioned by seller's negligence or based upon strict products liability or upon principles of indemnity or contribution. Content©2020 Ensign-Bickford Aerospace & Defense Company, Simsbury, CT 06070, U.S.A.